

ANALYSIS		%W/V	g/L
NUTRIENT			
Nitrogen (N) as urea		13.00	130.00
Phosphorus (P) as water soluble		11.00	110.00
Phosphorus (P) as potassium phosphate		4.0	40.00
Total Phosphorus (P)		15.0	150.00
Potassium (K) as potassium phosphate		15.0	150.00
as EDTA complex			
Magnesium (Mg)		0.03	0.30
Copper (Cu)		0.016	0.16
Iron (Fe)		0.16	1.60
Manganese (Mn)		0.031	0.31
Zinc (Zn)		0.031	0.31
Boron (B) as borax		0.06	0.60
Molybdenum (Mo) as sodium molybdate		0.016	0.16
Water		47.00%	
Total solids		69.00%	
Maximum Biuret Level		0.29%	

APPLICATION RATES
1-3 L/ha in a minimum of 200 Litres of water

ROOT DRENCH AND SOIL APPLICATION - As a general rule
1-2 times the foliar application rates

NPK 13-15-15 CONTAINS CHELATED MICRONUTRIENTS AND WHEN USED AS DIRECTED IS HIGHLY SUITED -
*To be used alone or as an adjunct to liquid Nitrogen fertilisers * For all irrigation systems * For foliar, root drench or soil applications * To help alleviate plant stress or nutritional disorders* For aerial application * To generally promote plant health, quality and yield * And is compatible with most agricultural chemicals

Optimum results will be obtained from several applications when applied to foliage. NPK 13-15-15 should be used during the cooler parts of the day. On certain plants, additional benefits may be obtained by the use of a good quality non-ionic wetting agent. For low volume or mister application a minimum of 20 litres of water per hectare is recommended.

If mixing with other chemicals, adhere to the following sequence- Water NPK 13-15-15-other chemical. (If compatibility is in doubt, mix a small amount in a suitable container and observe the results

RUTEK

RUTEK

DATE OF
MANUFACTURE

BATCH NO:

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING



NPK
13-15-15

LOW pH FORMULATION

20L 200L 1000L

Manufactured by

RUTEK PTY LTD

23 HARGRAVE STREET
TAMWORTH NSW 2340

GENERAL INSTRUCTIONS

MIXING AND SPRAYING

Shake the container thoroughly before use. Pour through the filter into the tank three quarters filled with water, whilst agitating. Top up with water and continue to agitate until spraying is completed.

PRECAUTIONS

Avoid application under extremes of climate eg. Rapid drying conditions, extremely slow drying conditions, frost rain or when frost or rain are anticipated

COMPATIBILITY

RUTEK products are widely compatible with many agricultural chemicals. Contact your distributor for information.

STORAGE AND DISPOSAL

Store in the closed original container, in a well-ventilated area as cool as possible. Protect from frost. Do not store for prolonged periods in direct sunlight.

Triple rinse containers before disposal and add hoses to tank mix or dispose of rinsate in a disposal pit away from desirable plants, their roots and watercourses.

On-site disposal of undiluted chemicals is unacceptable. Destroy empty containers by breaking, crushing or puncturing them. Dispose of the containers at a local authority landfill that does not burn its refuse. If there is no local authority landfill readily available in your area, bury the containers to a depth of 500mm or more at a licensed/approved disposal site. In some states wastes can only be buried at a licensed landfill. Do not burn empty containers or product.

SPILLAGE

Hose small spillage (less than 1 litre of concentrate) away with a large excess of water. Large spillage should not be directed to drains. Large spillage should be absorbed in sawdust or sand and the absorbent material containing the product disposed of in a sealed container at an approved disposal site.

PROTECTION OF WILDLIFE, FISH, CRUSTACEA AND ENVIRONMENT

Do NOT contaminate streams, rivers or waterways with the chemical or used containers.

SAFETY DIRECTIONS

Harmful if swallowed. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling. Avoid inhaling spray mist.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre Ph: 13 11 26. If in eyes, flush with water for 15 minutes and see a doctor.

EXCLUSION OF WARRANTIES AND LIMITATIONS OF LIABILITY

The purchaser acknowledges that no express or implied warranty, condition, description or representation is given or made by Rutek Pty Ltd (ABN 91 002 846 988) in relation to this product. To the maximum extent permitted by the law, all warranties, terms, conditions and any duty of care which would otherwise be implied or arise by operation of law, statute or use in relation to this product are hereby excluded as against any and all persons, whether purchasers of this product or not. To the maximum extent permitted by law, Rutek's total liability to any person in connection with this product, whether arising from a breach of any express or implied term, condition or warranty, any duty of care or otherwise, other than any liability which by these terms or otherwise is excluded, shall not exceed the amount paid by the purchaser to the vendor for this product, whether or not such liability results from or involves negligence on the part of Rutek.